

CP550-TP1

DATA SHEET



50HZ - THREE PHASE - PERKINS ENGINE

| | |
|-----------------------|-----------------------|
| Standby Power (kVA) | 550 |
| Standby Power (kW) | 440 |
| Prime Power (kVA) | 500 |
| Prime Power (kW) | 400 |
| Tank Size (l) | 708 |
| Noise (dB(A) @7m) | 80 |
| Weight (kg) | 4,846 |
| Dimensions LxWxH (mm) | 5,360 x 1,650 x 2,250 |

STANDARD FEATURES

- 4P ABB breaker
- Deepsea DSE7320 controller (AMF start)
- Double walled chassis (bundled)
- Emergency stop
- Factory filled with anti freeze/coolant
- Electric fuel level sensor
- Low fuel alarm
- Battery isolator
- Neutral bar
- Battery charger & jacket water heater
- Pre-wired for auto start
- Rain cap on exhaust
- Mechanical fuel gauge
- Lifting points
- 50 deg C tropical radiator

CANOPY FEATURES

- **Compatible with 2000/14/EC directives, certified noise emission level**
- Two or four lifting points depending on enclosure size
- Hidden exhaust inside the canopy with rain cap.
- Two emergency stop buttons. One on canopy and one on the controller.
- Improved air suction channel to ensure maximum cooling in the canopy
- Radiator air outlet and exhaust safely directed upwards
- Convenient access cover in enclosure for topping up radiator coolant.
- Durable powder coating on cabinet to protect against corrosion and rust
- Solid sound insulated cabinet for quiet operation

ENGINE DATA

CAPS generator sets use leading engine brands that have state of the art technology and have compliance with ISO 8528, ISO 3046, BS 5514, DIN 6271 standards. These engines offer low fuel consumption, provide accurate speed control with have mechanical or electronic type governors.

| | |
|--|-------------------------|
| Manufacturer | PERKINS |
| Model | 2506A-E15TAG2 |
| N° of Cylinders | INLINE |
| Cylinder Configuration | 6 |
| Displacement (l) | 15,2 |
| Bore (mm) | 137 |
| Stroke (mm) | 171 |
| Compression Ratio | 16:01 |
| Aspiration | TURBOCHARGE-INTERCOOLER |
| Governor Type | ELECTRONIC/ECM |
| Cooling System | WATER |
| Coolant Capacity (l) | 58 |
| Lubrication Oil Capacity (l) | 62 |
| Electrical System VDC | 24 |
| Speed / Frequency (rpm / Hz) | 1500 rpm / 50 Hz |
| Engine Gross Power (Standby 50 Hz) (kW) | 495 |
| Fuel Consumption %110 ESP (l/h) | 111 |
| Fuel Consumption %100 PRP (l/h) | 100 |
| Fuel Consumption %75 PRP (l/h) | 76 |
| Fuel Consumption %50 PRP (l/h) | 53 |
| Exhaust Outlet Temperature (°C) | 550 |
| Exhaust Gas Flow (m³/min) | 98 |
| Combustion Air Flow (m³/min) | 36,6 |
| Cooling Air Flow (m³/min) | 722 |

ALTERNATOR DATA

CAPS use global market leading Leroy Somer alternators with state of the art technology and manufactured to the highest quality for productivity and durability. Leroy Somer alternators, meet appropriate International Standards for alternators: EC 60034-1; CEI EN 60034-1; BS 4999-5000; VDE 0530, NF 51- 100,111; OVE M-10, NEMA MG 1.22.

They also feature maintenance free bearings with electronic type voltage regulators for voltage setting.

| | |
|-----------------------------|--|
| N° of Phases | 3 |
| Power Factor | 0.8 |
| N° of Bearings | SINGLE |
| N° of Poles | 4 |
| N° of Leads | 6-12 |
| Insulation Class | H-F |
| Degree of Protection | IP 21-23 |
| Excitation System | AVR (Automatic Voltage Regulator), Brushless |
| Connection Type | STAR - TRIANGLE |
| Manufacturer | LEROY-SOMER |
| Model | TAL047C |

CONTROL PANEL DSE-7320

FEATURES

- 4-Line back-lit LCD text display
- Five key menu navigation
- Front panel editing with PIN protection
- Customisable status screens
- Power save mode
- Support for up to three remote display units
- 9 configurable inputs
- 8 configurable outputs
- Flexible sender inputs
- Configurable timers and alarms
- 3 configurable maintenance alarms
- Multiple date and time scheduler
- Configurable event log (250)
- Tier 4 CAN engine support
- Integral PLC editor
- Easy access diagnostic page
- CAN and Magnetic Pick-up/Alt. sensing
- Fuel usage monitor and low fuel alarms
- Charge alternator failure alarm
- Manual speed control (on compatible CAN engines)
- Manual fuel pump control
- Engine exerciser
- "Protections disabled" feature
- kW & kV Ar protection
- Reverse power (kW & kV Ar) LED and LCD alarm indication
- Power monitoring (kW h, kV Ar, kV A h, kV Ar h)
- Load switching (load shedding and dummy load outputs)
- Automatic load transfer (DSE7320)
- Unbalanced load protection
- Independent Earth Fault trip
- True dual mutual standby with load balancing timer (DSE7310 only)
- USB connectivity
- Backed up real time clock
- Fully configurable via DSE Configuration Suite PC software
- Configurable display languages
- Remote SCADA monitoring via DSE Configuration Suite PC software
- User selectable RS232 and RS485 communications
- Configurable Gencomm pages
- Advanced SMS messaging (additional external modem required)
- Start & stop capability via SMS messaging
- Additional display screens to help with modem diagnostics
- Idle control for starting & stopping.
- DSENet@ expansion compatible
- Heated display option available



Due to a policy continuous improvement CAPS reserves the right to amend details and specifications without notice and all information given is subject to the CAPS" current condition of sales

FUNCTIONS

- AMF programmable controller
- Remote start controller
- Manual start controller
- Engine controller
- Remote display & control unit
- CTs at genset or load side

COMMUNICATION

- Web monitoring
- GSM-SMS (required externally modem)
- E-mail
- USB Device
- RS-232
- J1939-CANBUS

TOPOLOGIES

- 2 phase 3 wires, L1-L2
- 2 phase 3 wires, L1-L3
- 3 phase 3 wires
- 3 phase 4 wires, star
- 3 phase 4 wires, delta
- 1 phase 2 wires