

SDG300S-3A6

Specification

GENERATOR

Type	Dual Voltage (Manual parallel)
Frequency (Hz)	50 / 60
3-phase 4 wires	
- Prime Output (kVA)	270 / 300
- Standby Output (kVA)	297 / 330
- Voltage (V)	200/400 / 220/440
- Current (A)	779/390 / 787/394
Single-phase auxiliary output	
- Voltage (V)	100 / 110
- Dedicated terminals (kVA)	-
- Outlets (kVA)	1.5×4 / 1.65×4
Power factor (%)	3-phase 80 (lagging) / Single-phase 100

ENGINE

Make, Model	KOMATSU SAA6D125E-2-B
Type	Direct-Injection, Turbo-Charged, Intercooled
Rated output (kW)	232 / 257
Rated output (PS)	316 / 350
Rated speed (min-1)	1500 / 1800
Fuel tank capacity (L)	490
Engine oil amount (L)	62
Battery × quantity	170F51×2

DIMENSION & WEIGHT, etc

L×W×H (mm)	3900×1400×1760
Dry weight (kg)	3790
Operating weight (kg)	4290
Sound power level in decibels (dB)	95 / 98
Sound pressure level (dB[A])	66 / 69
Designated emissions regulation	JPN Stage 2

●Specifications are subject to change without notice.

